

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 1.5 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: **26 mm.**

Maximum acoustic insulation: **Rw = 39 dB.**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

**Class 3**

Water tightness (UNE-EN 12208:2000):

**Class 7A**

Wind resistance (UNE-EN 12210:2000):

**Class C5**

\*Reference test 1,20m x 1,20 m 2 sashes

SECTIONS	Frame: 60, 65, 77 and 80 mm Three-rail: 106 and 126 mm Sash: 33 and 37 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Window 1.5 mm	POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass : From 14.6 to 20 mm
MAXIMUM DIMENSIONS	Width (L) = 2,200 mm Height (H) = 2,600 mm	OPENING POSIBILITIES	Sliding door 2, 3, 4 and 6 sashes Optionally three-rail Optionally galandage mono-rail and two-rail with 1, 2 and 4 sashes
MAXIMUM WEIGHT/SASH	100 Kg Square cut assembly 200 Kg Wrap around sash		

Please consult maximum dimensions according to types.

## FINISHES

Colour powder coating  
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras  
Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

