



MEDITERRANEAN BALCONY

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 2.1 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **30 mm.**

Maximum acoustic insulation: **Rw = 35 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 3

Water tightness (UNE-EN 12208:2000):

Class 8A

Wind resistance (UNE-EN 12210:2000):

Class C4

*Reference test 1.49 x 1.24 m. 1 Sash + 1 fijo

SECTIONS	Frame 106 mm Three-rail 161 mm Sash 45 mm	EXTRUSION ALLOY 6063 T-5
PROFILE THICKNESS	Balcony 1.5 mm	OPENING POSIBILITIES Sliding mono-rail: - 1 Sash + 1 fix - 2 Sashes + 2 Fix Two-rail sliding door 2, 3 and 4 sashes Optionally galandage 1 and 2 sashes Optionally three-rail
MAXIMUM DIMENSIONS	Width (L) = 2,200 mm Height (H) = 2,600 mm	
MAXIMUM WEIGHT/SASH	240 Kg	

Please consult maximum dimensions according to types.

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

