

ENERGY EFFICIENCY

Thermal Transmission Coefficient
 U_w from 0.9 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **48 mm.**

Maximum acoustic insulation: **Rw = 46 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1200

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 1.31 x 1.48 m. 2 sashes.

SECTIONS	Frame 60 mm Sash 70 mm
PROFILE THICKNESS	Window 1.5 mm Balcony 1.7 mm
MAXIMUM DIMENSIONS	Width (L) = 1,600 mm Height (H) = 2,800 mm
MAXIMUM WEIGHT/SASH	150 Kg.

Please consult maximum dimensions according to types.

FINISHES	Colour powder coating (RAL, mottled, rough...) According Qualicoat > 60 microns
	Wood effect powder coating According to Qualideco standard
	Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured

EXTRUSION ALLOY
6063 T-5

POLYAMIDE STRIP LENGTH
Polyamide 6.6 reinforced with 25% fiberglass : 25 mm

GASKETS
EPDM triple gasket

FOAMS
Perimeter polyolefin foam in glazing rebate zone

OPENING POSIBILITIES	
INWARDS	Side hung, turn&tilt, bi-fold, tilt and parallel-tilt
OUTWARDS	Side hung and top hung

