

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 1,1 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing

## ACCUSTIC INSULATION

Maximum glazing: **45 mm**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207):

**Class 4**

Water tightness (UNE-EN 12208):

**Class 9A**

Wind resistance (UNE-EN 12210):

**Class A3**

Reference test: 2,700 x 2,530 mm. 3 sashes

Security test (PAS 24:2012):

**Complies**

Reference test: 3 sashes. Configuration 330. 2,701 x 2,517 mm.

<b>SECTIONS</b>	Frame 73 mm Sash 73 mm	<b>EXTRUSION ALLOY</b>	6063 T-5
<b>PROFILE THICKNESS</b>	Door 1,8 mm	<b>POLYAMIDE STRIP LENGTH</b>	Polyamide 6.6 reinforced with 25% fiberglass: Frame 20 mm Sash 30 mm
<b>MAXIMUM DIMENSIONS</b>	Width (L) = 1200 mm Height (H) = 3000 mm	<b>OPENING POSIBILITIES</b>	Interior: 1 to 14 sashes  Exterior: 1 to 14 sashes Possibility of corner sash at 90° without mullion
<b>MAXIMUM WEIGHT/SASH</b>	120 Kg	<b>ACCESSIBILITY</b>	Possibility of embedded low threshold
<b>FINISHES</b>	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured		

Please consult regarding maximum weight and dimensions according to types

