



# COR VISION SLIDING SYSTEM

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 1.3 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing

## ACCOUSTIC INSULATION

Maximum glazing: **30 mm**

Maximum acoustic insulation: **Rw = 41 dB**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN-12207):

**Class 4**

Water tightness (EN-12208):

**Class 7A**

Wind resistance (EN-12210):

**Class C5**

Reference test: Balcony 1.23 x 1.55 m, 1 sash + 1 fixed

SECTIONS	Frame 116 mm Tri-rails 182 mm Sash 37 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Door 1.7 mm	POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass from 16 to 24 mm
MAXIMUM DIMENSIONS	Width (L) = 2.500 mm Height (H) = 3.000 mm	OPENING POSSIBILITIES	Sliding 2, 3, 4 and 6 sashes. Optionally monorail and triple rail (1 sash+1 fixed) (2 sashes+1 fixed). Optionally corner sash at 90° without mullions. Galandage 1 and 2 sashes
MAXIMUM WEIGHT/SASH	320 Kg		
DRAINAGE	Optionally drainage system and drainage grid made of stainless steel		

Please consult regarding maximum weight and dimensions according to types

## FINISHES

Colour powder coating  
(RAL, mottled, rough...)

According to Qualicoat >60 micras

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras  
Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

